



Autonomous Mobility Appliqué System

Participants

COCOM Sponsor: CENTCOM

COCOM Co-Sponsor: TRANSCOM

Lead Service: US Army

Supporting Service: USMC

Oversight Executive: OUSD(AT&L)DDRE/RFD/CS/MK Tribbie

Technical Manager: US Army/TARDEC/Bernard Theisen

Operational Manager: CENTCOM/Anthony Lester

Deputy Operational Manager: CASCOM/Larry Perecko

Transition Manager: US Army/RS JPO/Ray Folden

Other Participants/Partners: MCCDC/MCWL





























Report Documentation Page		Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.				
1. REPORT DATE	2. REPORT TYPE	3. DATES COVERED		
22 APR 2013	Briefing Charts	03-03-2013 to 17-04-2013		
4. TITLE AND SUBTITLE				
Autonomous Mobility Applique System Joint Capability Technology Demonstration		5b. GRANT NUMBER		
		5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)		5d. PROJECT NUMBER		
Bernard Theisen; Anthony Lester; Larry Perecko; Ray Folden		5e. TASK NUMBER		
		5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army TARDEC,6501 East Eleven Mile Rd,Warren,Mi,48397-5000		8. PERFORMING ORGANIZATION REPORT NUMBER #23809		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army TARDEC, 6501 East Eleven Mile Rd, Warren, Mi, 48397-5000		10. SPONSOR/MONITOR'S ACRONYM(S) TARDEC		
		11. SPONSOR/MONITOR'S REPORT NUMBER(S) #23809		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited				
13. SUPPLEMENTARY NOTES				
Integrate robotic technology onto Tact physical load on the operator allowing The material solution would provide an By-Wire kit and an Autonomy kit. The interface and actuation necessary to im would provide scalable autonomy to in behaviors for convoy operations.	operator to focus on external threats a Autonomous Mobility Appliqu? Sy wehicle By-Wire kit will provide act aplement the Autonomy kits robotic	s and avoid vehicle accidents. stem (AMAS) comprised of a ive safety functionality and the capability. The Autonomy kit		

c. THIS PAGE

unclassified

17. LIMITATION OF

ABSTRACT

Public Release

18. NUMBER

OF PAGES

12

15. SUBJECT TERMS

a. REPORT

unclassified

16. SECURITY CLASSIFICATION OF:

b. ABSTRACT

unclassified

RESPONSIBLE PERSON

19a. NAME OF



Operational Problem Statement




- Current forces are facing an operational environment based on uncertainty, anti access and aerial
 denial threat tactics. This environment increases Soldier risk due to interdiction of US Lines Of
 Communication via hit-and-run and standoff attacks. As a result, these threats increase responsibility
 of drivers and passengers to maintain situational awareness along unsecured routes.
- Current Operating Environment requires service members to conduct logistic resupplies and operational patrols on specified Main Supply routes.
 - Inherit vulnerabilities that are hard to mitigate
 - Enemy forces are adapting to our convoy operational doctrine, TTPS, and SOPs
 - Speed and distance predictable to execute attacks against the convoys.
 - Majority of IED detection is done through visual means
 - Small Window of detection and evasive action
- Convoys are encountering environmental weather conditions that impact convoy operations leading to reduced logistics through-put and vehicle damage from on and off road accidents.
 - Convoys have been cancelled
 - Impacting Logistic and Operational patrols
 - Accidents due to fatigue and poor visibility
 - Human Limitations Restrict Effectiveness of Force.
- Current forces are operating and navigating vehicles alone over prolonged periods of time.
 - Increasing potential for accidents
 - Degradation of Performance
 - Task Overload

Increased Safety and Situational Awareness



AMAS JCTD (OV-1)







AMAS JCTD Technical Overview



- Integrate robotic technology onto Tactical vehicles to automate the driving task by providing scalable autonomy in a single material solution agnostic of platform.
 - Autonomy Kit
 - Autonomous Hardware and Sensors
 - By-Wire/Active Safety Kit (BWASK)
 - Vehicle Specific Devices to Retrofit Current Tactical Vehicles
 - Common Interfaces
 - Common Framework
- Scalable and flexible to address multiple task such as convoys, security, reconnaissance, sustainment, maneuver, maneuver support.
- Operational scenario using a secure mixed manned/unmanned platform convoy will demonstrate increased vehicle safety with high op tempo in complex conditions
 - Year One Platforms MTVR, M915 w/trailer
 - Year Two Platforms MTV, PLS w/flatrack, HET w/trailer
 - OCP AST Support MATV BWASK
- Conduct Technical Demos and Operational Demo (CONUS): Demonstrate Driver Assist and Robotic Capabilities.



AMAS JCTD Technical Approach



Year One

Integrate and Deploy Appliqué System:

- Define and Integrate Appliqué System
 - By-Wire/Active Safety Kits
 - 2 Each MTVR and M915 w/trailer
- Capability
 - Driver Assist/Active Safety Functionality
- Technical Deliverables
 - BWASKs on first 4 Vehicles
 - Open Architecture and Interfaces
 - Standardized Metrics and Test
 Procedures w/ATEC and MCCDC
 - LRU plug and play with limited adjustments

Year Two


Increase levels of Autonomy and Expand Platforms:

- Extend Kit Capability
 - 2 Each MTV, PLS w/flatrack and HET w/trailer
- Increase Capabilities in Autonomy Kit
 - Enhanced Driver Assist/Active Safety
 - Robotic Capability
- Technical Deliverables
 - Enhanced Autonomy Kit
 - Additional BWASKs
 - Scalable Autonomy
 - Improved Standardized Metrics and Test
 Procedures w/ATEC and MCCDC
 - Technical Specifications for Transition RFP
 - Framework for Validation of Realistic Requirements



AMAS Hardware Concept








AMAS Notional Hardware Implementation







Scalable Autonomy



FATTES OF LABOUR				
Level 1 Passive Safety	Level 2 Active Safety	Level 3 Convoy Behaviors	Level N Future (Enabled by JCTD)	
<u>Capabilities</u>	<u>Capabilities</u>	<u>Capabilities</u>	<u>Capabilities</u>	
Collision Warnings	Lane Keeping	• Leader/Follower	 Teleoperation 	
 Roll Over Warnings 	 Collision Avoidance 	Remote Control	 Go To Point Nav 	
 Stability Control 	Active Stability	 Waypoint Navigation 	 Dynamic Rerouting 	
Blind Spot Detection	Control	 Convoy Intrusion 	 Guided Vehicles 	
Lane Departure Warnings	Lane Change AssistAdaptive Cruise Control	 Convoy Rejoining 	 Collaborative Teaming 	
Pay-off	Pay-off	Pay-off	Pay-off(Mission Capabilities)	
 Improved Safety 	 Driver Augmentation 	• All Weather	 Perimeter Security 	
• Increase Capabilities of	• Improves Efficiency of	Operation	• Route Clearance	
inexperienced Drivers Driver		 Increase throughput and efficiencies 	 Persistent Stare 	
 Increase Situational Awareness 	Increased OpTempo	 Flexibility in convoy composition and routing 	Ordnance Detection	
, .			Decontamination	
			UNCLASSIFIED 8	



Overall Demonstration Strategy & Plan



Schedule

- Year One: Refinement and Integration
 - Develop Common Appliqué Kit
 - 1st Technical Demo Across Four Vehicles
 - -2 Each MTVR and M915 w/trailer.
 - Develop CONOPS / TTP and Finalize
- Year Two: Operational Assessment and Transition
 - 2nd Technical Demonstrations
 - Three Additional Platforms for 10 Total
 2 Each MTV, PLS w/flatrack and HET w/trailer
 - Integration of Lessons Learned
 - Begin ATEC Safety Release Process
 - Operational Demonstration
 - With Solders and Marines
 - Final Operational Demonstration Report

Tech Demonstrations and Operation Assessment

- Convoy Operations
 - Limited MSRs/ASRs
 - Long / Short Haul Duration
 - High Speeds/Low Speeds
- Operating conditions
 - Visibility/Terrain
 - Threat/Extreme Climates/Night Movements
- Full Spectrum Operations







Transition Strategy



AMAS JCTD Transition Paths:

1) Fieldable Prototypes

- Army Kits available for Extended User Evaluation (EUE) (after year 1 and year 2)
- Marine Corps vehicles available with integrated AMAS kits for EUE (after year 1 and year 2)

2) Spiral Software Capabilities to

- Husky Mounted Detection System PoR
- Route Clearance and Integration System PoR

3) SACO PoR

Army is pursuing a Pre-MS A MDD to start the SACO PoR

The AMAS JCTD Provides capabilities across robotic Programs of Record while providing residuals for Warfighter use



Summary



Technical Plan:

Integrate robotic technology onto Tactical vehicles to automate the driving task and reduce the
mental and physical load on the operator allowing operator to focus on external threats and avoid
vehicle accidents. The material solution would provide an Autonomous Mobility Appliqué System
(AMAS) comprised of a By-Wire kit and an Autonomy kit. The vehicle By-Wire kit will provide active
safety functionality and the interface and actuation necessary to implement the Autonomy kits robotic
capability. The Autonomy kit would provide scalable autonomy to include enhanced active safety
functionality and leader/follower behaviors for convoy operations.

Demonstration Approach:

- 2 Technical Demonstration
- 1 Operation Demonstration

Deliverables:

- Year 1: AMAS BWASKs w/common interfaces defined and driver assist capabilities.
- Year 2: AMAS Kits applied to additional platforms and additional levels of autonomy.

Transition:

FY14 with Milestone B and EMD Contract Award(s) OR CPD AROC/JROC Approval





